

Rubio Monocoat Universal Maintenance Oil

Universal maintenance oil for a refreshing and unique look

Universal Maintenance Oil is a maintenance oil for refreshing and better protecting wood treated with Rubio Monocoat oil, as well as for upgrading surfaces not treated with Rubio Monocoat. Universal Maintenance Oil gives the treated surface a soft satin gloss and increases its liquid resistance. The oil is therefore extremely suitable for 'high traffic' areas that require extra protection (e.g. public areas, offices, restaurants, hotels, etc.).



Universal Maintenance Oil is available in the colours 'Pure', 'White' and 'Black', to be chosen depending on the colour of the surface to be treated.

PRODUCT INFORMATION

› Specific characteristics

- Universal use
- Provides extra protection
- Adds shine
- 0% VOC

› Technical characteristics

- Physical state at 20°C: liquid
- Basis: mixture of natural oils
- Density: 0.93 - 1.4 g/cm³
- Flash point: > 65°C
- VOC content: 0 g/L

DRYING TIME	6 - 8 h
CURING TIME	48 h
APPLICATION INFORMATION	All already treated wooden surfaces indoors
CONSUMPTION	0,5 litre = 75-100 m ²
WORKING TEMPERATURE	8 - 30 °C
HUMIDITY APPLICATION RANGE	40 - 60%
STORAGE	The product can be stored for up to 12 months. Store in dry conditions and in the original packaging. Keep away from frost.
CLEANING	At the earliest after 48 hours with a damp cloth. After 7 days with Universal Soap or Surface Care.

REMARKS	Use very little product to prevent the surface from becoming sticky. Ensure adequate ventilation.
----------------	--

** These usages are merely indicative. Results depend on wood type and method of preparation. It is always recommended to make a sample in order to calculate the exact usage.*

APPLICATION INFORMATION

› Instructions for use

> Furniture, stairs & worktops

STEP 1. Make the floor free of dirt and dust.

STEP 2. Spray Rubio Monocoat Surface Care on the surface.

STEP 3. Clean the surface with a mop or Microfiber Pad.

STEP 4. Let the surface dry (± 15 minutes). Careful: do not leave water on the surface, it is sufficient to clean damp. Do not walk on the floor until it is completely dry.

STEP 5. Take the Universal Maintenance Oil and stir thoroughly until a homogeneous mixture is obtained.

STEP 6. Apply a small amount of oil with a brush and afterwards spread out with a beige or red Rubio Monocoat Scrubby pad or a hand sander with a small beige or red 5.9 inch Rubio Monocoat pad (you can also use the Rubio Monocoat Mouse Pad for smaller objects and corners). Preferably work in areas of 2 to 4 m² (areas which you can finish within ± 15 minutes, including the next step).

STEP 7. Allow to absorb for a few minutes and then wipe away all the excess oil with a cloth or a hand sander with a small white 5.9 inch Rubio Monocoat pad. Each treated area should be wiped dry within 15 minutes and should not feel sticky anymore.

> Floor

STEP 1. Make the floor free of dirt and dust.

STEP 2. Pour a maximum of 50 to 100 ml of Universal Soap in a bucket with 10 litres of water.

STEP 3. Clean the surface with a mop or Microfiber Pad.

- Tip: The best working method is with two buckets: one with the soap mixture and one with clean water to rinse the dirt out of the mop.

STEP 4. Rinse with clean water. Careful: do not leave water on the surface, it is sufficient to clean damp.

STEP 5. Allow to dry for ± 15 minutes. Do not walk on the floor until it is completely dry.

STEP 6. Take the Universal Maintenance Oil and stir thoroughly until a homogeneous mixture is obtained.

STEP 7. Work in areas of 5 to 10 m². Start each area by treating the edges with a beige or red Scrubby pad. Then apply a small amount of Universal Maintenance Oil every 0.5 metres with a brush. Spread in the direction of the wood with a polisher with a beige or red 16 inch pad.

STEP 8. Wipe away all the excess oil with a cloth or a polisher with a white 16 inch pad.

STEP 9. After you have finished all the areas, go over them again with a new white pad. The surface should not feel sticky anymore.

> Tips & Tricks

- Stir the product well before applying.
- When using several units on one site, it is recommended to mix them to obtain an even result.
- Maintenance with Rubio Monocoat Oil Plus 2C in the original colour is recommended as soon as the treated surface begins to show excessive wear or the colour needs to be refreshed.

> Packaging

Can 0.5 L





WARNING

Cloths and other tools, saturated with oil, may spontaneously combust. After usage, they need to be soaked in water before disposal.

REMARK

The product may not be diluted in any case!

> Related products



> Certificates



Check the packaging and the safety data sheet for more details.

For our complete assortment of products for the protection and colouring of interior and exterior wood, please visit www.rubiomonocoat.com

LIABILITY: It is the user's responsibility to establish, through his own tests, whether the product is suitable for the chosen application. In no case can Muylle Facon NV be held liable for any consequential damage. The information above may be subject to changes, which will be published in the updated versions of the technical data sheet. We cannot be held liable for poor results due to causes that are not related to the quality of the product. This technical information has been drawn up based on the currently available information and knowledge. The most recent technical data sheets can be requested or are available on the website. **Date of TDS: 11/04/2022. Check the safety information before using the product.**



Rubio[®] MONOCOAT

MUYLLE  FACON

Muylle Facon NV
Ambachtenstraat 58
8870 Izegem (BELGIUM)

Phone +32 (0) 51 30 80 54
Fax +32 (0) 51 30 99 78
info@muyllefacon.be

www.rubiomonocoat.com